

GYSBI- ITT-M

Request for Quotation Supply OF Doors for warehouse.

1. INTRODUCTION

Guyana Shore Base Inc. (GYSBI) invites qualified and experienced bidders to submit Quotation for the Supply and Delivery of Doors to replace the damaged and unserviceable doors in the warehouse for our facility at Industrial Estate (Plot7) McDoom, Houston, East Bank Demerara.

2. PRODUCT REQUIREMENTS

- Delivery Location: GYSBI Industrial Estate (Plot 7) Mc. Doom, Houston, East Bank Demerara.
- Objective: To Provide Doors to replace the damaged and unserviceable doors in the warehouse for our facility at Industrial Estate.
- Key Consideration: See below Technical Specification Table & drawing attached.

3. REQUIREMENTS FOR QUOTATION SUBMISSION

Interested contractors must provide the following documents:

- Local Content Certificate (if available). If no Local Content Certificate is available; Guyanese-registered businesses can provide evidence of majority-Guyanese ownership and indication that local content certification is being or will be pursued.
- Valid Business Registration or equivalent
- Valid GRA & NIS Compliance
- Any Other Certification

4. SUBMISSION DETAILS

- Date published: April 16 ,2025
- Deadline for Submission: May 14, 2025
- Submission Format: Single PDF document
- Submission Email Address: tenders@gysbi.com
- Clarifications & Queries: All inquiries can be submitted to the email address above

5. DISCLAIMER

This RFQ does not constitute a solicitation for bids or an offer to contract. Guyana Shore Base Inc. reserves the right to accept or reject any submission at its sole discretion and to proceed with the procurement in any manner it deems fit.

TECHNICAL SPECIFICATION

| Description of Requirement | Specification | Quantity |
|----------------------------|---|----------|
| Overhead Roll-up door | 5'2" Width x 16' Height, Standard lift, 220V, 60Hz motor with controls. Shall have sensing edge for door stop and hoist chain for manual operation. Shall have all the necessary hardware for complete installation and commissioning. Specifications as per the attached drawing. | 4 |
| Rubber Roll-up door | 25'2" Width x 16' Height, complete with all mounting hardware for installation. Input voltage 208-220V, 60Hz. Controller shall have self-diagnostics and be UL/NEMA rated. Shall feature infrared proximity and obstruction detection, reverse sensing edge, and door stop device. Door curtain operation speed 3ft/s-5ft/s, wind load tested up to 27 psf. Door curtain shall be Nitrile Butadiene or Styrene Butadiene Rubber. Door shall be outfitted with chain hoist | 4 |



| | | |
|--|---|--|
| | for manual operation. Shall break away from the side guides upon impact and reset and self-repair after an operation cycle. | |
|--|---|--|

Issued by:

GUYANA SHORE BASE INC. (GYSBI)

April 16, 2025